

HOLY CROSS CHURCH, RYTON GATESHEAD

The organ was built by Lewis & Co. in 1886. In 1906 Blackett & Howden added a Solo Organ and changed the manual actions from tracker to pneumatic, but the Lewis pipework was not changed. The Swell Horn, for which Lewis had made provision in 1886, was installed in 1911 by Harrison & Harrison, who also added a tremulant.

In 1990 Harrison & Harrison restored the organ to its 1886 specification, with new tracker actions in the original style.

GREAT ORGAN

Open Diapason		8
Lieblich Gedact		8
Salicional	(bass from Gedact)	8
Octave		4
Flute Harmonique		4
Flautina		2

SWELL ORGAN

Rohr Flöte		8
Geigen Principal	(bass from Rohr Flöte)	8
Viole de Gambe		8
Voix Célestes	(tenor g)	8
Geigen Principal		4
Horn		8
Oboe		8

PEDAL ORGAN

Open Diapason		16
Sub Bass		16

Couplers

Great to Pedal
Swell to Pedal
Swell to Great

Accessories

Tremulant (by pedal)
Three combination pedals to the Great Organ
Two combination pedals to the Swell Organ
Lever swell pedal

Manual compass 56 notes; pedal compass 30 notes

THE LEWIS ORGAN
RESTORED BY
HARRISON & HARRISON, 1990